

NOTE: Information herein is believed by Southwest Microwave, Inc. to be accurate. However, Southwest Microwave assumes no responsibility for any omissions or errors or inaccuracies for its use or for any infringements of patents or other rights of third parties that may result from its use. Data is intended for informational purpose only and does not constitute a contract of sale or any express or implied warranty, including any warranty of merchant ability or fitness for a particular purpose.






PIN/TAB 290-26P

DIELECTRIC 290-27D


APPLICATION

STRIPLINE TRANSITION LAUNCH



CATALOG CONNECTOR MODELS

211-03,-18,-26SF 212-03,-10,-25SF 213-03,-17,-30SF 214-03,-17,-30SF



PIN/TAB: BeCu

> UNS-C17300 PER ASTM-B-196/197. GOLD PLATE PER MIL-G-45204.

DIEL: VIRGIN TFE FLUOROCARBON PER

ASTM-D-1710, TYPE 1, GRADE 1, CLASS B, AND ASTM-D-1457.

MATERIAL & FINISH

REV: A4 ECN: 6300 DATE: 6-30-95

DRAWN APRVD. DATE DK 3-20-95 GH 3-20-95



Southwest Microwave, Inc. 9055 South McKerny Street Tempe, Arizona 85284-2946 Telephone (480) 783-0201 Fax (480) 783-0360

TITLE

290-26P-27D PIN/TAB, .020 DIA X .225L X .050 TAB WITH .125 LONG DIELECTRIC

DATE 3/95	DWG.	NO.	7
SHEET			/

9B53777

REV. Α5