
NOTE: Information herein is believed by Southwest Microwave, Inc. to be accurate. However, Southwest Microwave assumes no responsibility for any omissions or errors or inaccuracies for its use or for any infringements of patents or other rights of third parties that may result from its use. Data is intended for informational purpose only and does not constitute a contract of sale or any express or implied warranty, including any warranty of merchant ability or fitness for a particular purpose.



HOUSING AND METAL CONTACT RING:	STEEL, CRES ALLOY UNS—S30300 PER ASTM—A582. PASSIVATE PER QQ—P—35.			
CONTACT:	T: BeCu UNS-C17300 PER ASTM-B-196/197 GOLD PLATE PER MIL-G-45204			
DIELECTRIC INSULATOR:	VIRGIN TFE FLUOROCARBON PER ASTM-D-1710 AND ASTM-D-1457			
BEAD RING:	ULTEM 1000 PER ASTM-D-5205			
MATERIAL & FINISH				

- 2. INTERFACE I.A.W. MIL-STD-348
- 1. ALL DIMENSIONS ARE IN INCHES, ALL ANGLES ARE IN DEGREES. DIMENSIONS SHOWN IN BRACKETS [XXX] ARE MILLIMETERS.

TOLERANCES ARE BASED UPON DIMENSIONS IN INCHES. METRIC DIMENSIONS ARE FOR "REFERENCE ONLY".

NOTES: UNLESS (OTHERWISE	SPECIFIED
-----------------	-----------	-----------

SOUTHWEST MICROWAVE

CONTACT GAGING SPEC. N SOCKET	91C54030
CONTACT GAGING SPEC015 SOCKET	91B52103
SPECIFICATIONS	91C58956
SPECIFICATION GROUP	DRAWING NO.

	0,00	EAG		Microwave,	
REV	ECN: 8785	INIT:	DATE: 5/13/09	APRVD.	DATE: 5/15/09

Southwest Microwave, Inc. 9055 South McKemy Street Tempe, Arizona 85284-2946 Telephone (480) 783-0201 Fax (480) 783-0360

	Ω 4		N.I	14014	11/1			_
ULIEM	CA	PIURE	IN	JACK	-11/1	165Q	FLANGE	<u>.</u>
	TO	ACCEP	Τ	(.036)	DIA.	PIN		

DRN BY: EJO	DATE: 9/05	MODEL NO. 710 07CF	REV.
EJO	9/05	517-()/>-	l –
SCALE:	3:1	012 0701	ΙK
SHEET: 1	OF 1	DWG. NO. 79C58701	