

HOUSING AND COUPLING NUT: STEEL, CRES ALLOY UNS-S30300 PER ASTM-A582. PASSIVATE PER QQ-P-35.

CONTACT: BeCu UNS-C17300 PER ASTM-B-196/197. GOLD PLATE PER MIL-G-45204.

DIELECTRIC: ULTEM 1000 PER ASTM-D-5205. KEL-F PER MIL-P-46036.


RETAINING RING: BeCu UNS-C17300 PER ASTM-B-196/197.

GASKET: SILICONE RUBBER PER ZZ-R-765.

CONTACT SPECIFICATION	91P52120
SPECIFICATIONS	91Y54305
INTERFACE 2.40mm JACK	91P53661
INTERFACE 2.92mm PLUG	91K52018
SPECIFICATION GROUP	DRAWING NO.

MATERIAL & FINISH

REV: A5 ECN: 7258 DATE: 1/18/00 *wudc*  
 REV: A4 ECN: 7253 DATE: 1-11-00 EJO  
 REV: A3 ECN: 7198 DATE: 9-3-99 EJO

DRAWN DK	DATE 4/10/96	APRVD. <i>wudc</i>	DATE 1/18/00	TITLE 101430-00SF 2.92mm PLUG TO 2.40mm JACK ADAPTER
 Southwest Microwave, Inc. 9055 South McKemy Street Tempe, Arizona 85284-2946 Telephone (480) 783-0201 Fax (480) 783-0360				SCALE <b>5:1</b> SHEET <b>1 OF 1</b>
DWG. NO. <b>79Y54303</b>			REV. <b>A5</b>	