
MODEL No.:

17500-4003P

NOTE: Information herein is believed by Southwest Microwave, Inc. to be accurate. However, Southwest Microwave assumes no responsibility for any omissions or errors or inaccuracies for its use or for any infringements of patents or other rights of third parties that may result from its use. Data is intended for informational purpose only and does not constitute a contract of sale or any express or implied warranty, including any warranty of merchant ability or fitness for a particular purpose.



5. MATERIAL AND FINISH:

SHELL - ALUMINUM ALLOY 6061 PER ASTM B221. ELECTROLESS NICKEL FINISH PER ASTM B733-90.


INSULATOR - ULTEM 1000 PER ASTM D5205

RETAING CLIPS - BeCu ALLOY UNS-C17200 PER ASTM B194.

POTTING COMPOUND - EPOXY

MOUNTING HARDWARE - STAINLESS STEEL SER 300 PER SAE-AMS-QQ-S-763. PASSIVATED FINISH PER ASTM A967.

- 4. CONTACT CAVITIES WILL ALSO ACCEPT SIGNAL SOCKET COAX CONTACTS PER MIL-C-39029/64.
- 3. ALL SSBP AND SIGNAL CONTACTS ARE INSERTABLE AND REMOVEABLE USING STANDARD M81969/39-01 INSERTION/EXTRACTION TOOL.
- 2. EXTERNAL CONFIG. I.A.W. MIL-DTL-83513
- 1. ALL DIMENSIONS ARE IN INCHES. ALL ANGLES ARE IN DEGREES. DIMENSIONS SHOWN IN BRACKETS [XXX] ARE IN MILLIMETERS.



SUPERCEDES SKDH4074 7/1/14 Southwest Microwave, Inc. 9055 South McKemy Street Tempe, Arizona 85284-2946

MICROWAVE

Telephone (480) 783-0201

Fax (480) 783-0360

MICRO-D RECEPTACLE 6 POSITION FOR SSBP-20HD COAX PIN CONTACTS

66049

DRN BY: DATE: E.OLSEN 7/1/14 SCALE: 2:1	MODEL NO. 17500-4003P	REV.
SHEET: 1 OF 1	DWG. NO. 79BP61711	A

NOTES: UNLESS OTHERWISE SPECIFIED.