


- HOUSING: STEEL, CRES ALLOY UNS-S30300 PER ASTM-A582. PASSIVATE PER QQ-P-35.
- COUPLING NUT: STEEL, CRES ALLOY UNS-S30300 PER ASTM-A582. PASSIVATE PER QQ-P-35.
- CONTACT: BeCu UNS-C17300 PER ASTM-B-196/197. GOLD PLATE PER MIL-G-45204.
- DIELECTRIC: ULTEM 1000 PER ASTM-D-5205.
- DIELECTRIC: KEL-F PER MIL-P-46036.
- RETAINING RING: BeCu UNS-C17300 PER ASTM-B-196/197.
- GASKET: SILICONE RUBBER PER ZZ-R-765.

MATERIAL & FINISH

CONTACT GAGING SPEC.	91P52120
SPECIFICATIONS	91P56682
INTERFACE-2.40 JACK	91P53661
INTERFACE-3.5 PLUG	91F56689
SPECIFICATION GROUP	DRAWING NO.

A	RELEASE	11/7/00	WMC
REV.	ECN	DESCRIPTION	DATE APPVD
TITLE		61430-00SF	
		2.40mm JACK TO 3.5mm PLUG ADAPTER	
SCALE	3:1	DWG. NO.	79Y56420
SHEET	1 OF 1	REV.	A

DRAWN	EJO	DATE	6/20/00	APRVD.	WMC	DATE	11/14/00
 <p>Southwest Microwave, Inc.          9055 South McKemy Street          Tempe, Arizona 85284-2946          Telephone (480) 783-0201          Fax (480) 783-0360</p>							