
DWG No.:

## 91Y60922

NOTE: Information herein is believed by Southwest Microwave, Inc. to be accurate. However, Southwest Microwave assumes no responsibility for any omissions or errors or inaccuracies for its use or for any infringements of patents or other rights of third parties that may result from its use. Data is intended for informational purpose only and does not constitute a contract of sale or any express or implied warranty, including any warranty of merchant ability or fitness for a particular purpose.




2.40 CONNECTOR		
ITEM	MATERIAL & FINISH	
CAPTURE BEAD:	ULTEM 1000 PER ASTM D5205	
BEAD:	KEL-F (PCTFE) PER ASTM D1430	
CONTACT:	BeCu UNS-C17300 PER ASTM B196 GOLD PLATE PER ASTM B488	
HOUSING:	STEEL, CRES ALLOY UNS-30300 PER ASTM A582 PASSIVATED PER ASTM A967-99	

TRANSITION BLOCK, GROUNDING PLATE, THREADED CLAMPING PLATE	C360 BRASS ALLOY UNS-C36000 PER ASTM B16. NICKEL PLATE PER AMS 2404B	
LAUNCH PIN:	BeCu UNS-C17300 PER ASTM B196 GOLD PLATE PER MIL-DTL-45204	
TRANSITION BLOCK DIELECTRIC:	VIRGIN PTFE FLUOROCARBON PER ASTM D1710, TYPE 1 GRADE 1, CLASS B	
ITEM	MATERIAL & FINISH	
TRANSITION BLOCK		

1. ALL DIMENSIONS ARE IN INCHES. ALL ANGLES ARE IN DEGREES. DIMENSIONS SHOWN IN BRACKETS [XXX] ARE IN MILLIMETERS.

NOTES: UNLESS OTHERWISE SPECIFIED.



TITLE



AJS

Southwest Microwave, Inc. 9055 South McKerry Street Tempe. Arizona 85284-2946 Telephone (480) 783-0201 Fax-(480) 783-0360

1/21/16

2.40mm JACK (FEMALE) END LAUNCH CONNECTOR LOW PROFILE

DRN BY DATE: 09/26/12 DWG. NO.

91Y60922 SHEET: 1 OF 1

B

REV.