


50255010-01G

NOTE: Information herein is believed by Southwest Microwave, Inc. to be accurate. However, Southwest Microwave assumes no









OUTER AND CENTER CONTACT:	BeCu ALLOY UNS-C17300 TEMPER TH04 PER ASTM B196/197 GOLD PLATE PER MIL-DTL-45204, TYPE II, GRADE C, .000060/.000090 THICK OVER ELECTROLESS NICKEL PER MIL-C-26074 .000070/.000120 THICK.	
BUSHING:	BeCu ALLOY UNS-C17300 TEMPER TH04 PER ASTM B196/197 GOLD PLATE PER MIL-DTL-45204, TYPE II, GRADE C .000025/.000040 THICK OVER ELECTROLESS NICKEL PER MIL-C-26074 .000050/.000100 THICK.	
DIELECTRIC:	VIRGIN PTFE FLUOROCARBON PER ASTM D1710, TYPE 1 GRADE 1, CLASS B	
SSBB DIELECTRIC: PEEK-HT		
CAPTURE BEAD:	TURE BEAD: ULTEM 1000 PER ASTM D5205	
ITEM MATERIAL & FINISH		

- 2. CONNECTOR DESIGN IS COMPATIBLE WITH CURRENT MATERIAL REQUIREMENTS FOR RoHS III AND WEEE PER EUROPEAN COMMUNITY DIRECTIVE 2015/863/EU.
- 1. ALL DIMENSIONS ARE IN INCHES. ALL ANGLES ARE IN DEGREES. DIMENSIONS SHOWN IN BRACKETS [XXX] ARE IN MILLIMETERS.

NOTES: UNLESS OTHERWISE SPECIFIED.

REV A	RELEASE	APRVDE	DATE: /21/23	TITLE
SOUTHWEST MICROWAVE		Southwest I 9055 South Mo Tempe, Arizon	•	DRN BY: JAC
		Telephone (48)	0) 783-0201	SCALE:
		Fax (480) 783-	0360	CHEET: 1

Fax (480) 783-0360

50255010-01G SSBP SIZE 16 PIN TO SSBB20 RECPT (J) ADP

RN BY: DATE: DWG. NO. 02/17/23 SCALE: SHEET: 1 OF 1

79BP70044

REV.